STIEBEL ELTRON Simply the Best

Tankless Water Heater Accessories Anti-Scale Hard Water Conditioner STREET THROS with Template Assisted Crystallization Isolation Valve Kit Descaling Kit

Accessories

FOR TANKLESS ELECTRIC WATER HEATERS

- > Prevent Scale and Sediment Buildup
- > Simplify Maintenance Procedures
- > Extend Service Life
- Maintain Performance

- Simplify maintenance
- Maintain performance
- Protect your investment

Tankless water heater accessories from Stiebel Eltron offer protection and ease of maintenance

Isolation Valve Kit

- Allows easy servicing & maintenance
- > Easy to install

Isolating valves make it easy to service a tankless electric water heater and clean the cold water inlet filter screen. Our kit puts all the components needed in an easy-to-install package. Pressure relief valve is included for use in unique situations but are not required for most tankless water heater installations.



- Lead-free construction
-) 3/4" NPT connections
- > Includes inlet & outlet isolating valves & pressure relief valve

Flow-aide Descaling Kit

- > Removes mineral scale, lime, and rust
- > Restores lost performance

If a tankless water heater has lost performance due to hard water mineral deposits, a Flow-aide tankless descaling kit offers the answer. Featuring a biodegradable descaling solution and submersible pump for easy operation, the Flow-aide descaling kit may also be used as routine preventative maintenance or as part of a complete system with the Scale TAC-ler water conditioner.

Flow-Aide fluid is available by the quart as a refill kit.

- Lead-free construction
-) 3/4" NPT connections for easy use
- › Biodegradeable and eco-friendly
- Safe for potable water lines
- > 20x stonger than citric acid-based or vinegar cleaners





Scale TAC-ler

Template Assisted Crystallization Water Conditioner

- Salt-free water conditioner compatible with all tankless and conventional tank-style water heaters
- > Most effective of all non-salt water conditioners at preventing mineral scale
- > Nothing reduces water heater efficiency more than mineral scale

Scale TAC-ler water conditioner is compatible with all tankless and conventional tank-style water heaters. Scale TAC-ler is installed on the cold water inlet of the water heater, where it treats the water entering the water heater. It will provide protection for flow rates up to 6 gallons per minute.

Hard water mineral scale accumulating on heating elements slowly reduces performance. It affects both heat transfer and water pressure. Preventing mineral scale formation ensures your water heater's optimal performance, increasing service life, and possible preventing premature failure.

If water hardness exceeds 7 grains per gallon (GPG) or 120 mg/l (PPM) hard water treatment should be considered. If hardness exceeds 12 GPG or 200 mg/l (PPM), treatment is strongly recommended. Water heaters with existing mineral scale build-up should be treated with the Flow-Aide de-scaling system to restore original performance. Scale TAC-ler will prevent future mineral build-up.

- Protects from harmful hard water scale
-) Protects manufacturer's warranty coverage
- > Protects equipment investment
- > Ensures optimal performance and efficiency
- Maintains water pressure and flow rates
- Does not add chemicals to the water
-) Does not change the taste, smell, or feel of the water
- Environmentally friendly
- Simple installation
- > No daily maintenance
- No salt, backwashing, chemical regeneration, or brine discharge
- Does not remove beneficial minerals
- Ideal for all tankless or tank-type water heaters
- > Built-in sediment pre-filter

How It Works

Scale TAC-ler salt-free water conditioners use a specialized polymeric bead medium that serves as a catalyst for the formation of calcium and magnesium carbonate nano-crystals. Instead of forming hard mineral scale on surfaces, these microscopic crystals of calcium and magnesium carbonate remain suspended in solution and pass through to the drain. This process is called Template Assisted Crystallization, or "TAC." A university study determined that TAC technology was the most effective of all non-salt water conditioners at preventing mineral scale, with reduction levels consistently in excess of 90%. TAC technology passes the German DVGW W512 standard for water treatment.

These pictures show water heating elements exposed to hard water.

Note the mineral build-up on the element exposed to untreated water vs. the element protected by TAC treatment.









Scale TAC-ler Water Conditioner Technical Data

| Model | Scale TAC-ler |
|--|---|
| Item number | 692442 |
| Filter type | Template Assisted Crystallization (TAC) |
| Max. treatment service flow rate | 6.0 gpm (22.7 l/min) |
| Max. flow rate through device | 10.0 gpm (37.85 l/min) |
| Max. water pressure | 90 psi (6.2 bar) |
| Min. water pressure | 30 psi (2 bar) |
| Temperature range | 40-100°F (4-38°C) |
| Dimensions (H x W x D) | 24 ¹ / ₂ " x 18 ¹ / ₈ " x 8" (622 x 460 x 203 mm) |
| Connection type | 3/4" NPT |
| Valve type | Ball |
| Material | Plastic |
| Approx. cartridge life | 2 years |
| Replacement filter cartridge | Item Number 692443 |
| pH range | 6.5-8.5 |
| Optimal hardness level for treatment | 0.4-1.8 gpg (7-30 mg/l) |
| Max. treatable hardness level | 75 gpg (1,283 mg/l [ppm]) |
| Max. acceptable levels of contaminates in incoming water | Chlorine: < 3 mg/l (ppm) Hydrogen Peroxide: < 0.5 mg/l (ppm) Iron: < 0.3 mg/l (ppm) Manganese: < 0.05 mg/l (ppm) Copper: < 1.3 mg/l (ppm) Hydrogen Sulfide (H ₂ S): must be removed Polyphosphates and Oils: must be removed |
| Water treatment certification | NSF/ANSI 61 |

Isolation Valve Kit Technical Data

| Model | Lead-free Brass Isolation Valve Kit |
|-------------------------------|--|
| Item number | 540444 |
| Connection type | 3/4" NPT |
| Kit includes | Inlet Isolating Valve Outlet Isolating Valve Pressure Relief Valve |
| Valve type | Ball |
| Material | Forged Brass |
| Water treatment certification | NSF/ANSI 61-G & NSF/ANSI 372 |

Flow-Aide Descaling Kit Technical Data

| Model | Flow-Aide Descaling Kit |
|-------------------------------|--|
| Item Number | 540000 |
| Flow-Aide fluid refill | 1 Qt. Item #540002 |
| Connection type | 3/4″ NPT |
| Kit includes | 3½ gal. bucket 350 gph pump 2 5'-hoses 1 qt. solution |
| Water treatment certification | NSF/ANSI 60 |

Stiebel Eltron Family of Energy Saving Water Heating Products



Efficient tankless electric water heaters

Distributed by:



Point-of-use Tankless



Whole House



Stiebel Eltron's plant in Holzminden, Germany.

Stiebel Eltron has been a world leader in the development of advanced water heating technology since 1924. Our pursuit of engineering excellence and high-quality manufacturing results in products fulfilling the highest expectations of performance and reliability. They are...Simply the Best.





Solar hot water



Heat Pump Water Heaters



energy domestic hot water systems

STIEBEL ELTRON

17 West Street
West Hatfield, MA 01088
TOLL FREE 800.582.8423
PHONE 413.247.3380
FAX 413.247.3369
info@stiebel-eltron-usa.com
www.stiebel-eltron-usa.com

Due to our continuous process of engineering and technological advancement, specifications may change without notice.